

DECLARATION of PERFORMANCE (DoP)

According to Construction Products Regulation: (EU) 305/2011
EN 14566:2008+A1: 2009

DoP nr.: **SBS.ZBS.2025.001**



1. Unique identification code of the product type.

QZ, Fixmart, Private label and neutral drywall screws and selfdrilling screws according to article range:
215, 217, 230, 231, 232, 233, 234, 236, 237, 238, 239, 241, 243, 244, 245, 246, 247, 248, 269, 315, 317, 324, 330, 331, 332, 333, 340, 341, 343, 344, 345, 346, 347, 348, 815, 817, 824, 830, 831, 832, 833, 836, 837, 838, 839, 840, 841, 843, 844, 845, 846, 847, 848, 915, 917, 930, 931, 932, 933, 934, 940, 941, 943, 944, 945, 946, 947, 948.

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4).

See packing / product label

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Mechanical fasteners for gypsum plasterboard systems and metal sheet/sections

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

GebuVolco B.V.
Christiaan Huygensweg 7
3225 LD Hellevoetsluis
Netherlands

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

-

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard.

EN 14566+A1: 2009 + The manufacturer performed the Initial Type Testing (ITT) conform System 4 and installed a Factory Production Control (FPC) in accordance with the requirements of EN ISO 9001

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Safety in case of fire	A1	EN 13501-1:2007+A1:2009

Essential characteristics	Performance	Harmonised technical specification
Withdrawal force	>450N	EN 14566:2008+A1:2009
Flexural strength test	PASS	EN 14566:2008+A1:2009
Hardness	HRC55, minimum depth of 0.05mm	EN 14566:2008+A1:2009

10. On behalf of the manufacturer:

D. de Pijper, General Director
GebuVolco
P.O. Box 112
3220 AC Hellevoetsluis
Tel. +31-181-330000

DECLARATION of PERFORMANCE (DoP)

According to Construction Products Regulation: (EU) 305/2011
EN 14566:2008+A1: 2009

DoP nr.:

SBS.ZBS.2025.001



Artikelgroups **215, 217, 230, 231, 232, 233, 234, 236, 237, 238, 239, 241, 243, 244, 245, 246, 247, 248, 269, 315, 317, 324, 330, 331, 332, 333, 340, 341, 343, 344, 345, 346, 347, 348, 815, 817, 824, 830, 831, 832, 833, 836, 837, 838, 839, 840, 841, 843, 844, 845, 846, 847, 848, 915, 917, 930, 931, 932, 933, 934, 940, 941, 943, 944, 945, 946, 947, 948.**

Diameter x length:

2.5 x 60	3.9 x 16	4.2 x 25	4.8 x 32	5.5 x 22	6.3 x 60
2.5 x 100	3.9 x 19	4.2 x 32	4.8 x 38	5.5 x 25	6.3 x 63
	3.9 x 25	4.2 x 38	4.8 x 50	5.5 x 32	6.3 x 75
3.5 x 9,5	3.9 x 30	4.2 x 45	4.8 x 60	5.5 x 38	
3.5 x 13	3.9 x 32	4.2 x 50	4.8 x 70	5.5 x 50	
3.5 x 16	3.9 x 35	4.2 x 55	4.8 x 90	5.5 x 63	
3.5 x 19	3.9 x 38	4.2 x 63	4.8 x 100	5.5 x 75	
3.5 x 25	3.9 x 45	4.2 x 65	4.8 x 110		
3.5 x 32	3.9 x 55	4.2 x 75	4.8 x 120	6.3 x 16	
3.5 x 35		4.2 x 85	4.8 x 130	6.3 x 19	
3.5 x 45	4.2 x 13		4.8 x 140	6.3 x 25	
3.5 x 55	4.2 x 14	4.8 x 13	4.8 x 150	6.3 x 32	
	4.2 x 16	4.8 x 16		6.3 x 38	
3.9 x 12	4.2 x 19	4.8 x 19	5.5 x 16	6.3 x 45	
3.9 x 13	4.2 x 22	4.8 x 25	5.5 x 19	6.3 x 50	