

DECLARATION of PERFORMANCE (DoP)

According to Construction Products Regulation: (EU) 305/2011
EN 14592+A1; June 2012



DoP no.: **SPS.RVS.2025.001**

Published on August 1, 2025.

1. Unique identification code of the product type.

QZ, Fixmart, Private Label and neutral (DTL)
Stainless steel chipboard screws (also collated)
according to article range: **203, 204, 221, 222, 223, 225, 226, 303, 304, 321, 322, 323, 325, 326, 803, 804, 821, 822, 823, 825, 826, 903, 904, 921, 922, 925, 926.**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4).

See packing / productlabel

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Mechanical fasteners for use in timber constructions

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

GebuVolco B.V.
Christiaan Huygensweg 7
3225 LD Hellevoetsluis
Netherlands

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

-

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard.

FPC nr.: W3 = 1034-CPD-2048/1/2013 W4 = 1034-CPD-2050/1/2012
W8 = 1034-CPD-2085/1/2013 W9 = 1034-CPD-2086/1/2013

EN 14592+A1; June 2012
Notified body 1034

W5 = 1034-CPD-2049/1/2012
W10 = 1034-CPD-2087/1/2013

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance

See page 2*

10. On behalf of the manufacturer:

D. de Pijper, General Director

GebuVolco
P.O. Box 112
3220 AC Hellevoetsluis
Tel. +31-181-330000

DECLARATION of PERFORMANCE (DoP)

According to Construction Products Regulation: (EU) 305/2011
EN 14592+A1; June 2012

DoP no.: **SPS.RVS.2025.001**

Published on August 1, 2025.



Article groups **203, 204, 221, 222, 223, 225, 226,**
303, 304, 321, 322, 323, 325, 326,
803, 804, 821, 822, 823, 825, 826,
903, 904, 921, 922, 923, 925, 926.

Diameter: **3.0, 3.5, 4.0, 4.5, 5.0, 6.0**

* 9. Declared performance

Essential characteristic	Performance
Pull-out resistance	See table per diameter
Head pull-through strength	5 mm: 7.9 kN
	6 mm: 11 kN
	8 mm: 20 kN
	10 mm: 28 kN
Tensile strength screw	Same as head pull-through
Torsional resistance	5 mm: 5.6 Nm
	6 mm: 9.5 Nm
	8 mm: 22 Nm
	10 mm: 40 Nm
Bending angle / ductility	≥ 45° (d0.7 + 20° per diameter)
Corrosion resistance	Stainless steel A2 / A4
Reaction to fire	Euroclass A1